

Load || BN 157151, BN 157151C0001; BN 157157; BN 157157C0001



Part number	BN 157151	BN 157151C0001	BN 157157	BN 157157C0001
Version	Panel mount and hand-held	Panel mount	Panel mount and hand-held	Panel mount
Interface type	4.3-10 socket (50Ω) per IEC 61169-54		7-16 socket (50 Ω) per IEC 61169-4	
VSWR, max.	1.20 @ 0.25 to 3.8 GHz			
Frequency range	0.25 to 3.8 GHz			
Intermodulation (IM3) @ 2x 20W, max.	-165 dBc			
Intermodulation (IM3) @ 2x 20W, typ.	-170 dBc			
Average power rating, max.	50 W			
Inner conductor material / surface finish	copper alloy / silver plated			
Outer conductor material / surface finish	copper alloy / silver plated			
Other metal parts / surface finish	copper alloy / CuSnZn plated stainless steel / no finish			
Case material / surface finish	aluminum / no finish			
Insulation	PTFE			
Weight, approx.	3.0 kg			
Ambient temperature range	-10 to +40 °C full power			
Relative humidity, max.	95% (non-condensing)			
Operating position	any, cooling slots not covered			
Scope of delivery	protective cap (all versions) handle and pads (157151, 157157 only)			

Load || BN 157151, BN 157151C0001; BN 157157; BN 157157C0001

